

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 19 S., R. 8 W.

CHAINS	
	A fir, 40 ins. dia., bears N.62°W., 79 lks. dist., marked $\frac{1}{2}$ S B T.
44.75	Gulch, c S., about 300 ft. below divide.
46.50	Ridge, c S., 200 ft. up.
48.00	Fir, 60 ins. diam.
53.00	Gulch, c S., 175 ft. down.
60.00	Fir, 40 ins. diam.
64.50	Divide, c S., 200 ft. up; thence along South slope.
80.00	Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for cor. to secs. 34, 35, 2 & 3, marked T 19 S S 35 on NE., R 8 W S 2 on SE., T 20 S S 3 on SW., S 34 on NW. face, with 2 notches on East and 4 notches on West edges; from which A dogwood, 8 ins. dia., bears N.16°E., 123 lks. dist., marked T 19 S R 8 W S 35 B T. A fir, 18 ins. dia., bears S.15 $\frac{1}{2}$ °E., 17 lks. dist., marked T 20 S R 8 W S 2 B T. A fir, 30 ins. dia., bears S.85°W., 31 lks. dist., marked T 20 S R 8 W S 3 B T. A fir, 12 ins. dia., bears N.21°W., 108 lks. dist., marked T 19 S R 8 W S 34 B T. Aug. 28th, '91.

N.88°47'West, on true S. boundary of Sec. 34.

Va.20°27'E. at 8 a.m.

Ascend.

3.21	Wall of sandstone, 8 ft. high, c N. & S.
3.75	Ridge, c NE. & SW., 150 ft. above corner.
5.15	Fir, 16 ins. diam.
18.50	Fir, 12 ins. diam.
25.50	Stream, 4 lks. wide, c NW., 550 ft. down.
31.80	Stream, 3 lks. wide, c NE.
35.70	Find post about 4 ins. diam., firmly set in ground, marked $\frac{1}{2}$ S on N. face; from which A fir, 10 ins. dia., bears S.82 $\frac{1}{2}$ °W., 24 lks. dist.,