

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 19 S., R. 8 W.

CHAINS	
10.50	Spur, c N., 100 ft. up.
20.30	Stream, 4 lks. wide, c S.60°W., 200 ft. below spur.
32.75	Stream, 5 lks. wide, c S., 175 ft. lower; ascend.
40.00	Set stone, 12x7x6 ins., 8 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A fir, 36 ins. dia., bears N.23°E., 87 lks. dist., marked $\frac{1}{4}$ S B T. An alder, 30 ins. dia., bears S.22°E., 39 lks. dist., marked $\frac{1}{4}$ S B T.
49.04	A fir, 70 ins. diam.
51.50	A ridge, c S., about 400 ft. above stream.
57.00	Divide, c N.70°E. & S.70°W.; descend.
61.75	Gulch, c N., 150 ft. down.
68.25	Divide, c NW. & SE., 200 ft. up.
80.00	Set post, 4 ft. long, 4 ins. square, 24 ins. in ground, for cor. to secs. 4, 5, 32. & 33, marked T 19 S S 33 on NE., R 8 W S 4 on SE., T 20 S S 5 on SW., and S 32 on NW. faces, with 4 notches on E. & 2 notches on W. edges; from which A fir, 24 ins. diam., brs. N.51°E., 43 lks. dist., marked T 19 S R 8 W S 33 B T. A fir, 24 ins. diam., brs. S.16 $\frac{1}{2}$ °E., 29 lks. dist., marked T 20 S R 8 W S 4 B T. A fir, 36 ins. diam., brs. S.51°W., 27 lks. dist., marked T 20 S R 8 W S 5 B T. A fir, 18 ins. diam., brs. N.16 $\frac{1}{2}$ °W., 47 lks. dist., marked T 19 S R 8 W S 32 B T.

Aug. 29th, '91.

N.88°47'W., on true S. boundary of Sec. 32.

Va.20°24'E. at 8 a.m.

Descend.

15.65	Stream, 7 lks. wide, c SW., 250 ft. below corner; ascend.
19.10	Stream, 3 lks. wide, c SE., about 150 ft. up.
31.75	Ridge, c S., 200 ft. above stream.