

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 19 S., R. 8 W.

CHAINS 40.00	Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A fir, 14 ins. dia., bears N.53°W., 13 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 14 ins. dia., bears S.73°E., 13 lks. dist., marked $\frac{1}{4}$ S B T.
44.00	Stream, 8 lks. wide, c S., 350 ft. below ridge.
54.00	Ridge, c S., 300 ft. above stream.
65.00	Stream, 12 lks. wide, c S., 300 ft. down.
69.50	Fir, 40 ins. diam.
80.00	400 ft. above stream. Set post, 4 ins. sq., 4 ft. long, 24 ins. in ground, for cor. to secs. 31, 32, 5 & 6, marked T 19 S S 32 on NE., R 8 W S 5 on SE., T 20 S S 6 on SW., S 31 on NW. faces, with 1 notch on west and 5 notches on E. edges; from which A fir, 30 ins. dia., bears N.36 $\frac{1}{2}$ °E., 43 lks. dist., marked T 19 S R 8 W S 32 B T. A fir, 12 ins. dia., bears S.71 $\frac{1}{2}$ °E., 32 lks. dist., marked T 20 S R 8 W S 5 B T. A fir, 18 ins. dia., bears S.14 $\frac{3}{4}$ °W., 34 lks. dist., marked T 20 S R 8 W S 6 B T. A fir, 24 ins. dia., bears N.4°W., 35 lks. dist., marked T 19 S R 8 W S 31 B T.
<hr/>	
	N.88°47'W., on true S. boundary of Sec. 31.
	Va. at 11 a.m. 20°23'E.
	Ascend.
1.50	Ridge, c NE. & S.70°W., 80 ft. above corner.
7.75	Fir, 36 ins. dia., on ridge, c N.70°W. & S.70°E.
14.20	Same ridge, c N.70°E. and S.70°W., 150 ft. higher.
20.65	Spur, c N.
29.25	Spur, c N.
38.00	Stream, 5 lks. wide, c N., 300 ft. below last spur.
40.00	Set post, 4 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which