

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 19 S., R. 8 W.

CHAINS

A fir, 14 ins. dia., bears S.56°W., 40 lks. dist.,
marked $\frac{1}{2}$ S B T.

A fir, 20 ins. dia., bears N.14 $\frac{1}{2}$ °W., 35 lks. dist.,
marked $\frac{1}{2}$ S B T.

49.00 Ridge, c. NW., 275 ft. above stream; thence down along
near top of a spur or ridge, course mainly West.

97.50 The NW. cor. of T. 20 S., R. 8 W., on the N. slope of
said ridge, which is a post about 6 ins. sq., standing
4 ft. above ground, marked T 19 S R 8 W S 31 on NE., T
20 S R 8 W S 6 on SE., T 20 S R 9 W S 1 on SW., T 19 S
R 9 W S 36 on NW. faces, with 6 notches on each edge;
from which

A fir, 36 ins. diam., brs. N.48°E., 23 lks. dist.,
marked T 19 S R 8 W S 31 B T.

A fir, 20 ins. dia., brs. S.7°E., 43 lks. dist.,
marked T 20 S R 8 W S 6 B T.

A hemlock, 9 ins. dia., brs. S.80°W., 37 lks. dist.,
marked T 20 S R 9 W S 1 B T.

A fir, 30 ins. dia., bears N.53°W., 72 lks. dist.,
marked T 19 S R 9 W S 36 B T.

Aug. 30th, '91.

Subdivisions of T. 19 S., R. 8 W.
Survey by Charles M. Collier under Contract 580 dated
June 23rd, 1891.

Survey commenced July 31st, 1891.

Having run the East line of Sec. 36 yesterday and having
made observation on Polaris the night before, I pro-
ceed at once to the SE. cor. of T. 19 S., R. 8 W.

Thence I run S.89°47'W., along S. boundary of Sec. 36.

Va.20°39'E.

At 40.00 chs. I find $\frac{1}{2}$ sec. cor. 10 lks. South and at
79.75 chs. find the cor. to secs. 1, 2, 35 & 36, 30
lks. N. of my line.

The true course of the S. boundary of Sec. 36 is, there-
fore, West and the length 79.75 chs.