

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS 22.50	Onto bench sloping West, 120 ft. below spur.
35.60	Stream, 2 lks. wide, c SW.
39.90	Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A maple, 10 ins. dia., bears N.7 $\frac{1}{4}$ °W., 58 lks. dist., marked $\frac{1}{4}$ S B T. An alder, 18 ins. dia., bears S.23 $\frac{1}{2}$ °W., 48 lks. dist., marked $\frac{1}{4}$ S B T.
41.85	Stream, 8 lks. wide, c NW., about 200 ft. below bench; ascend very steep.
49.20	Fir, 36 ins. diam.
49.85	Top of spur, c N., 250 ft. above stream; descend very steep.
56.80	Stream, 4 lks. wide, c N.10°E., 200 ft. below spur; ascend very steep.
67.75	Onto ridge, c N.80°E. & S.80°W., 350 ft. above stream; thence along N. slope of same.
79.80	To cor. to secs. 23, 24, 25 & 26.

From the cor. to secs. 2, 3, 34 & 35, on S. boundary of
Tp. I ran

N.2°W., bet. secs. 34 & 35.

Va. observed at 8 a.m. 20°27'E.

Ascend steep.

3.08	Fir, 48 ins. diam.
4.50	Top of ridge, c E. & SW., divide bet. Siuslaw and Smith River, 100 ft. above cor.; thence down along steep irregular and precipitous E. side of ridge.
40.00	Set post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which A cedar, 12 ins. diam., brs. N.12°W., 102 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 18 ins. diam., brs. N.4°E., 46 lks. dist., marked $\frac{1}{4}$ S B T.
52.00	Ridge, c N.30°E., about 500 ft. below divide; descend