

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

on steep NW. slope.

63.50 Into canyon, c NE., 350 ft. below ridge.

70.00 Top of spur, c NE., about 100 ft. above canyon; descend steep.

76.00 Enter bottom of Esmond Creek, 250 ft. below last spur.

79.70 Esmond Creek, 15 lks. wide, c W.

80.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 26, 27, 34 & 35, marked T 19 S S 26 on NE., R 8 W S 35 on SE., S 34 on SW., S 27 on NW. faces, with one notch on S. and 2 notches on E. edges; from which

An alder, 24 ins. diam., bears N.80½°E., 38 lks. dist., marked T 19 S R 8 W S 26 B T.

A vine maple, 5 ins. diam., bears S.37½°E., 49 lks. dist., marked T 19 S R 8 W S 35 B T.

A vine maple, 4 ins. diam., bears S.18°W., 60 lks. dist., marked T 19 S R 8 W S 34 B T.

An alder, 12 ins. diam., bears N.2°W., 30 lks. dist., marked T 19 S R 8 W S 27 B T.

S.88°47'E., on random line, bet. secs. 26 & 35.

Va.20°35'E. at 11:30 a.m.

40.00 Set temp. ¼ sec. cor.

79.60 Intersect N. & S. line, 25 lks. N. of temp. cor. to secs. 35, 36, 25 & 26.

N.88°26'W., on true line, bet. secs. 26 & 35.

Va.20°27'E. at 1:30 p.m.

4.00 Esmond Creek, 15 lks. wide, c NW.

5.10 Another part of same, 7 lks. wide, c N.; ascend steep.

12.00 Top of ascent on N. slope, about 250 ft. up; descend.

17.00 Into hollow, c NE., about 100 ft. down; ascend very steep.

23.50 Top of spur, c N.50°E., about 250 ft. up; descend.

39.80 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for ¼ sec. cor., marked ¼ S on N. face; from which

A fir, 24 ins. dia., bears S.41½°W., 10 lks. dist.,