

Subdivisions of T. 19 S., R. 8 W.

CHAINS

ascend steep along S. side of a ravine.

77.75 Top of ridge, c N. & S., 450 ft. above canyon; descend.

79.50 To cor. to secs. 22, 23, 26 & 27.

Sept. 9, '91.

N.2°W., bet. secs. 22 & 23.

Va.20°45'E. at 8 a.m.

On W. slope.

16.00 Top of spur, N.50°W.; thence across hollow, c W.

34.00 Top of ridge, c N.30°W.; thence down along steep E. side
of same.40.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from whichA fir, 12 ins. diam., bears S.69 $\frac{1}{2}$ °W., 57 lks. dist.,
marked $\frac{1}{4}$ S B T.A fir, 18 ins. diam., bears S.24°E., 46 lks. dist.,
marked $\frac{1}{4}$ S B T.

Continue down along E. side of ridge.

61.00 Stream, 4 lks. wide, c N.70°E., in a little bottom.

66.00 Leave bottom; ascend.

74.00 Top of ascent on E. slope, 150 ft. above stream; descend
steep.80.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for
cor. to secs. 22, 23, 14 & 15, marked T 19 S S 14 on
NE., R 8 W S 23 on SE., S 22 on SW., S 15 on NW. faces,
with 3 notches on S. and 2 notches on E. edges; from
whichA maple, 24 ins. diam., brs. N.85°E., 100 lks. dist.,
marked T 19 S R 8 W S 14 B T.A maple, 14 ins. diam., bears S.29°E., 92 lks. dist.,
marked T 19 S R 8 W S 23 B T.A maple, 8 ins. diam., bears S.41°W., 72 lks. dist.,
marked T 19 S R 8 W S 22 B T.A maple, 24 ins. diam., bears N.18 $\frac{1}{2}$ °W., 51 lks. dist.,
marked T 19 S R 8 W S 15 B T.

Sept. 10, '91.