

Subdivisions of T. 19 S., R. 8 W.

CHAINS

- N.3°W., bet. secs. 33 & 34.
 Va.20°33'E. at 8 a.m.
- 12.00 Fir, 48 ins. diam.
- 13.75 Ridge, c N.30°W. & S.30°E.
- 25.00 Spur of same, c E.
- 27.25 Hollow, c E.
- 30.25 Spur of same ridge, c E.
- 33.75 Ravine E.
- 39.00 Ridge, c NE. & SW.
- 40.00 Fir, 18 ins. diam. on W. side of top of ridge, which I
 marked for $\frac{1}{4}$ sec. cor., $\frac{1}{4}$ S on W. face; from which
 A fir, 24 ins. diam., bears N.68°E., 27 lks. dist.,
 marked $\frac{1}{4}$ S B T.
 A fir, 16 ins. diam., bears S.63°W., 33 lks. dist.,
 marked $\frac{1}{4}$ S B T.
- 43.30 Fir, 18 ins. dia., on top of ridge, c N.20°W. & S.20°E.
- 47.50 Spur, c down E.
- 54.50 Spur, c down NE.; descend very steep.
- 63.25 Stream, 1 lk. wide, c NE.
- 67.50 Top of spur, c NE.; descend very steep.
- 73.25 Stream, 15 lks. wide, c W., about 1000 ft. below S. end
 of the line; thence in bottom.
- 80.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for
 cor. to secs. 27, 28, 33 & 34, marked T 19 S S 27 on
 NE., R 8 W S 34 on SE., S 33 on SW., S 28 on NW. faces,
 with 3 notches on E. and 1 notch on S. edges; from
 which
 A fir, 40 ins. diam., bears N.58 $\frac{1}{2}$ °E., 79 lks. dist.,
 marked T 19 S R 8 W S 27 B T.
 A fir, 36 ins. diam., bears S.80 $\frac{1}{2}$ °E., 42 lks. dist.,
 marked T 19 S R 8 W S 34 B T.
 A fir, 24 ins. diam., bears S.12°W., 108 lks. dist.,
 marked T 19 S R 8 W S 33 B T.
 A fir, 16 ins. diam., bears N.2 $\frac{1}{2}$ °W., 53 lks. dist.,
 marked T 19 S R 8 W S 28 B T.