

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS
79.40

Intersect N. & S. line, 17 lks. N. of cor. to secs. 22,
23, 26, & 27.

Thence I run

N.88°40'W., on true line, bet. secs. 22 & 27.

Va. observed at 10 a.m. 20°44'E.

Descend from cor. very steep.

5.04 Fir, 48 ins. diam.

6.30 Ravine N.30°W., 240 ft. below cor.; ascend very steep.

10.85 Top of spur, c N., 150 ft. high; descend steep.

15.85 Ravine, c N.; ascend very steep.

26.25 Top of ridge or spur, c N.60°E., 400 ft. high; descend.

31.00 Ravine, c N.30°E., 150 ft. down; ascend very steep.

34.50 Top of spur, c N.30°E., 150 ft. up; descend.

39.70 Set post, 4 ft. long, 3 ins. sq., 24 ins. in the ground,

for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which

A fir, 38 ins. dia., bears S.39 $\frac{1}{2}$ °W., 19 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 24 ins. dia., bears N.26°E., 29 lks. dist.,
marked $\frac{1}{4}$ S B T.

41.50 Ravine, c N., 200 ft. below last spur.

44.50 Stream, 1 lk. wide, c N.30°E.; ascend steep.

46.40 Cedar, 18 ins. diam.

60.00 Onto flat topped ridge, 400 ft. above last stream, c

N.80°E. and S.40°E., divide bet. Esmond Creek and

Siuslaw; a ridge also runs from here North; thence

along near top of divide.

71.40 Fir, 30 ins. diam.

75.00 On top of spur, c N.40°W.; descend very steep.

77.25 Fir, 30 ins. diam.

79.40 To cor. to secs. 21, 22, 27 & 28, 150 ft. below last spur.

N.3°W., bet. secs. 21 & 22.

Va. 20°30'E. at 11:30 a.m.

Ascend out of hollow in partial deadening.

3.00 Spur, c N.50°W.

6.07 Fir, 24 ins. diam.; descend very steep.