

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

- 40.00 Set temp. $\frac{1}{2}$ sec. cor.
- 79.50 Intersect N. & S. line, 20 lks. N. of cor. to secs. 14, 15, 22 & 23.
- Thence I run
- N.88°38'W., on true line, bet. secs. 15 & 22.
- Va.20°35'E. observed at 10 a.m.
- Ascend along steep S. side of canyon.
- In heavy timber, mostly dead.
- 20.00 Ridge, NW. & SE., 450 ft. above cor.
- 38.75 Top of same ridge, c N.60°E. & S.20°W.; thence along N. side of same, over hollows and spurs thereof.
- 39.75 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{2}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which
- A fir, 40 ins. diam., bears S.75°W., 30 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 48 ins. diam., bears N.50°E., 13 lks. dist., marked $\frac{1}{4}$ S B T.
- 50.00 A spur, c N.
- 59.00 A spur, c N.
- 64.00 Ravine, c NE.
- 69.00 Top of ridge or spur, c N.; descend steep.
- 79.50 To cor. to secs. 15, 16, 21 & 22.
-
- N.3'W., bet. secs. 15 & 16.
- Va. observed at 12:30 p.m. 20°28'E.
- .50 Maple, 8 ins. diam.
- 10.00 Hollow, c W.
- 16.65 Fir, 80 ins. diam.
- 22.25 Fir, 86 ins. diam.
- 30.00 Top of spur, c W.
- 33.05 Maple, 12 ins. diam.
- 40.00 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{2}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- A fir, 30 ins. diam., bears S.31 $\frac{1}{2}$ °E., 91 lks. dist., marked $\frac{1}{4}$ S B T.