

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

A chinquapin, 7 ins. diam., bears N.45°W., 13 lks. dist., marked $\frac{1}{2}$ S B T.

Continue along W. slope of ridge.

60.00 Descend.

70.25 Stream, 2 lks. wide, c NW.; ascend along W. slope.

77.50 Top of ascent; descend.

80.00 Fir, 20 ins. diam., which I mark for cor. to secs. 15, 16, 9 & 10, T 19 S S 10 on NE., R 8 W S 15 on SE., S 16 on SW., S 9 on NW. faces, with 4 notches on S. and 3 notches on E. edges; from which

A fir, 12 ins. diam., bears N.74 $\frac{1}{2}$ °E., 25 lks. dist., marked T 19 S R 8 W S 10 B T.

A fir, 18 ins. diam., bears S.51 $\frac{1}{2}$ °E., 50 lks. dist., marked T 19 S R 8 W S 15 B T.

A fir, 8 ins. diam., bears S.56 $\frac{1}{2}$ °W., 40 lks. dist., marked T 19 S R 8 W S 16 B T.

A fir, 18 ins. diam., bears N.20°W., 21 lks. dist., marked T 19 S R 8 W S 9 B T.

Sept. 17th, '91.

S.88°47'E., on random line, bet. secs. 10 & 15.

Va. observed at 7 a.m. 20°33'E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.30 Intersect N. & S. line at cor. to secs. 10, 11, 14 & 15.

Thence I run

N.88°47'W., on true line, bet. secs. 10 & 15.

Va. observed at 9 a.m. 20°49'E.

1.50 Top of spur, c S.10°W.; thence over rolling table land.

2.68 Fir, 24 ins. diam.

13.00 Stream, 4 lks. wide, c S.80°E.

19.50 Same, 4 lks. wide, c N.80°E.

39.65 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which

A fir, 12 ins. diam., bears N.35°E., 22 lks. dist., marked $\frac{1}{4}$ S B T.