

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS	
62.25	Enter bottom, about 250 ft. below ridge; leave burnt timber.
63.70	Maple, 48 ins. diam.
64.00	Stream, 25 lks. wide, c NE.
72.00	Leave bottom; ascend.
78.75	Top of spur, c NW.
79.25	To cor. to secs. 28, 29, 32 & 33.
<hr/>	
	N.4'W., bet. secs. 28 & 29.
	Va.20°20'E. at 11:30 a.m.
	Ascend.
12.00	Top of ridge, c N.10°E.
17.00	Top of ridge, c N.20°W.
25.00	Top of ridge, c N.30°E.; descend steep.
32.75	Cedar, 60 ins. diam.
33.25	Enter little bottom.
34.00	Stream, 4 lks. wide, c E.
40.00	Set post in edge of bottom, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which A cedar, 12 ins. diam., bears S.17°E., 30 lks. dist., marked $\frac{1}{4}$ S B T. A chittem, 6 ins. diam., bears N.88 $\frac{1}{2}$ °W., 16 lks. dist., marked $\frac{1}{4}$ S B T.
	Ascend.
52.00	Spur, c S.30°E.
58.50	Spur, c E.
61.75	Spur, c NE.
67.75	Hollow, c E.
69.25	Top of spur; descend.
72.50	Enter bottom of Esmond Creek.
80.00	Fir, 36 ins. diam., which I mark for cor. to secs. 20, 21, 28 & 29, T 19 S S 21 on NE., R 8 W S 28 on SE., S 29 on SW., S 20 on NW. faces, with 4 notches on E. and 2 notches on S. edges; from which