

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

A fir, 18 ins. diam., bears N.77°E., 29 lks. dist.,
marked T 19 S R 8 W S 21 B T.

A fir, 60 ins. diam., bears S.63 $\frac{3}{8}$ °E., 50 lks. dist.,
marked T 19 S R 8 W S 28 B T.

A maple, 18 ins. diam., bears S.18 $\frac{3}{4}$ °W., 97 lks. dist.,
marked T 19 S R 8 W S 29 B T.

A maple, 16 ins. diam., bears N.72°W., 50 lks. dist.,
marked T 19 S R 8 W S 20 B T.

Sept. 22nd; '91.

S.88°47'E., on random line, bet. secs. 21 & 28.

Va.20°33'E. at 8 a.m.

40.00 Set temp. $\frac{1}{2}$ sec. cor.

79.30 Intersect N. & S. line, 10 lks. S. of cor. to secs. 21,
22, 27 & 28; thence

N.88°51'W., on true line, bet. secs. 21 & 28.

Va.20°30'E. at 11:30 a.m.

9.90 Fir, 16 ins. diam.

10.50 Ravine, c N., at forks, one from S.50°E., the other from
S.20°W.; ascend.

17.25 Top of ascent on N. slope; descend steep.

20.00 Stream, 1 lk. wide, c N.10°E.; ascend very steep.

25.75 Ridge, c N.; descend steep.

30.75 Ravine, c N.; ascend very steep.

32.50 Fir, 18 ins. diam.

35.75 Ridge, c N.

39.62 $\frac{1}{2}$ Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{2}$ S on N. face; from which

A fir, 36 ins. dia., bears N.79 $\frac{1}{2}$ °W., 60 lks. dist.,
marked $\frac{1}{2}$ S B T.

A maple, 20 ins. dia., bears S.45°W., 36 lks. dist.,
marked $\frac{1}{2}$ S B T.

50.75 Top of spur; c N.80°W.; descend steep.

74.25 Enter bottom of Esmond Creek.

77.00 Esmond Creek, 25 lks. wide, c N.