

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS
79.30

The cor. to secs. 20, 21, 28 & 29.

N.4°W., bet. secs. 20 & 21.

Va. 20° 26'E. at 2 p.m.

5.00 Stream, 4 lks. wide, c E.

8.50 Fir, 40 ins. diam.

Leave bottom; ascend gradually.

8.80 Hemlock, 30 ins. diam.

18.95 Fir, 12 ins. diam.

28.00 Top of ridge, c E. & W.

40.00 Set post, 4 ft. long, 3 ins. sq., 24 ins. in ground, for
¼ sec. cor., marked ¼ S on W. face; from whichA fir, 24 ins. diam., bears S.88½°E., 63 lks. dist.,
marked ¼ S B T.A fir, 30 ins. diam., bears N.43°W., 25 lks. dist.,
marked ¼ S B T. On N. slope.

42.50 A hollow, c E.; ascend steep.

54.00 Top of ridge, c E.; descend along W. slope.

69.00 Enter little bottom, c NE.

70.15 Stream, 4 lks. wide, c N.50°E.; ascend.

80.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground,
for cor. to secs. 16, 17, 20 & 21, marked T 19 S S 16
on NE., R 8 W S 21 on SE., S 20 on SW. & S 17 on NW.
faces, with 3 notches on S. and 4 notches on E. edges;
from whichA fir, 18 ins. diam., bears N.76½°E., 49 lks. dist.,
marked T 19 S R 8 W S 16 B T.A fir, 18 ins. diam., bears S.41°E., 25 lks. dist.,
marked T 19 S R 8 W S 21 B T.A fir, 24 ins. diam., bears S.84°W., 29 lks. dist.,
marked T 19 S R 8 W S 20 B T.A fir, 24 ins. diam., bears N.64°W., 23 lks. dist.,
marked T 19 S R 8 W S 17 B T.

Sept. 23, '91.