

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS	
40.00	Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which A fir, 12 ins. diam., bears N.37°E., 31 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 24 ins. diam., bears N.73 $\frac{1}{2}$ °W., 22 lks. dist., marked $\frac{1}{4}$ S B T.
44.00	Enter bottom, 350 ft. below top of ridge.
45.50	Stream, 12 lks. wide, c S.80°E., rock bottom.
47.50	Leave bottom; ascend gradually.
57.00	Stream, 3 lks. wide, c S.10°W. from N.
60.00	Leave stream, 3 lks. wide, c from N.10°E.
66.75	Highest of "The two high buttes" hrs. S.82 $\frac{1}{2}$ °W.
68.00	Onto ridge, c E. & W., 300 ft. above creek; descend very steep.
77.50	Into gully, c NW.; thence along very steep W. slope.
80.00	Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for cor. to secs. 16, 17, 8 & 9, marked T 19 S S 9 on NE., R 8 W S 16 on SE., S 17 on SW. and S 8 on NW. faces, with 4 notches on E. & S edges; from which A fir, 36 ins. diam., bears N.61°E., 75 lks. dist., marked T 19 S R 8 W S 9 B T. A fir, 48 ins. diam., bears S.29°E., 117 lks. dist., marked T 19 S R 8 W S 16 B T. A fir, 20 ins. diam., bears S.45 $\frac{1}{2}$ °W., 25 lks. dist., marked T 19 S R 8 W S 17 B T. A fir, 36 ins. diam., bears N.51°W., 30 lks. dist., marked T 19 S R 8 W S 8 B T.

Sept. 27th, '91.

S.88°47'E., on random line, bet. secs. 9 & 16.

Va.20°33'E. at 8 a.m.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.22 Intersect N. & S. line, 30 lks. S. of cor. to secs. 9, 10, 15 & 16; thence

N.89°W., on true line, bet. secs. 9 & 16.