

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

$\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which

A fir, 30 ins. diam., bears N.49 $\frac{1}{2}$ °W., 40 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 40 ins. diam., bears N.67 $\frac{1}{2}$ °E., 169 lks. dist.,
marked $\frac{1}{4}$ S B T.

Thence along E. slope of ridge.

55.00 Descend very steep.

63.75 Stream, 2 lks. wide, c E., 280 ft. down.

65.75 Stream, 4 lks. wide, c S.20°E.; ascend steep.

80.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for
cor. to secs. 8, 9, 4 & 5, marked T 19 S S 4 on NE.,
R 8 W S 9 on SE., S 8 on SW., S 5 on NW. faces, with 5
notches on S. and 4 notches on E. edges; from which

A fir, 6 ins. diam., bears N.31 $\frac{3}{4}$ °E., 68 lks. dist.,
marked T 19 S R 8 W S 4 B T.

A fir, 24 ins. diam., bears S.44 $\frac{3}{4}$ °E., 141 lks. dist.,
marked T 19 S R 8 W S 9 B T.

A fir, 36 ins. diam., bears S.69°W., 82 lks. dist.,
marked T 19 S R 8 W S 8 B T.

A fir, 18 ins. diam., bears N.21 $\frac{3}{4}$ °W., 116 lks. dist.,
marked T 19 S R 8 W S 5 B T.

Sept. 28th, '91.

From cor. to secs. 5, 6, 31 & 32, on S. boundary of T.

19 S., R. 8 W., I run

N.5°W., bet. secs. 31 & 32.

Va. observed at 7 a.m. 20°26'E.

Ascend on E. slope.

1.50 Fir, 24 ins. diam.

2.50 Spur, c NE.; thence along N. slope.

9.15 Fir, 16 ins. diam.

12.25 Stream, 1 lk. wide, c E.; thence along down E. slope.

17.00 Stream, 5 lks. wide, c SE.; ascend steep West slope.

33.00 Stream, 1 lk. wide, c W.

40.00 A dogwood, 10 ins. diam., which I mark for $\frac{1}{4}$ sec. cor.,