

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS
39.75

Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which

A maple, 12 ins. diam., bears N.35°W., 25 lks. dist., marked $\frac{1}{4}$ S B T.

A fir, 30 ins. diam., bears S.67 $\frac{1}{2}$ °E., 25 lks. dist., marked $\frac{1}{4}$ S B T.

47.00 Ravine, c N.50°E.

52.00 Ravine, c SE. up along gentle SE. slope.

74.50 Ridge, c NE. & SW.; descend.

79.50 To cor. to secs. 29, 30, 31 & 32.

Sept. 30, '91.

N.88°47'W., on random line, bet. secs. 30 & 31.
Va.20°23'E. at 7 a.m.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

97.40 Intersect W. boundary of Tp., 31 lks. N. of cor. to secs. 30 & 31.

Thence S.88°57'E., on true line, bet. secs. 30 & 31.
Va.20°34' at 11 a.m.

1.65 Fir, 18 ins. diam.

10.00 Descend gently.

21.50 Stream, 4 lks. wide, c S.; ascend steep out of stream; thence along steep irregular N. slope.

57.40 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which

A cedar, 12 ins. dia., bears S.65 $\frac{1}{2}$ °W., 22 lks. dist., marked $\frac{1}{4}$ S B T.

A fir, 18 ins. dia., bears N.74 $\frac{1}{2}$ °E., 14 lks. dist., marked $\frac{1}{4}$ S B T.

58.65 Fir, 36 ins. diam.

69.90 Stream, 2 lks. wide, c N.

77.75 Fir, 20 ins. diam.

84.25 Ravine, c N.70°W.

94.00 Spur, N.40°W.

97.40 Cor. to secs. 31, 32, 29 & 30.