

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

- Va. $20^{\circ}33'$ at 8 a.m.
- 2.00 Hollow, c E.; ascend.
- 12.00 Ridge, c E. & W., 250 ft. up.
- 20.75 Hollow, c E., 200 ft. down; ascend.
- 24.00 Top of ascent, 100 ft. up; thence along table land with E. slope.
- 40.00 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which
 A cedar, 18 ins. dia., bears $N.7^{\circ}E.$, 23 lks. dist., marked $\frac{1}{4}$ S B T.
 A fir, 30 ins. diam., bears $N.20^{\circ}W.$, 57 lks. dist., marked $\frac{1}{4}$ S B T.
 Descend steep.
- 43.00 Into a slide canyon, c $S.70^{\circ}E.$, 100 ft. down a little stream, comes in from a branch canyon just above from NW.; ascend.
- 51.10 Fir, 30 ins. diam.
- 55.25 Stream, 2 lks. wide, c $S.20^{\circ}W.$, in a slide canyon; continue to ascend steep.
- 66.00 Top of a ridge, c E. & W., 600 ft. up; thence descend along W. side of a little canyon running N.
- 80.00 300 ft. below ridge, set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for cor. to secs. 17, 18, 19 & 20, marked T 19 S S 17 on NE., R 8 W S 20 on SE., S 19 on SW., S 18 on NW. faces, with 5 notches on E. and 3 notches on S. edges; from which
 A fir, 7 ins. diam., bears $N.55\frac{3}{4}^{\circ}E.$, 115 lks. dist., marked T 19 S R 8 W S 17 B T.
 A maple, 8 ins. diam., bears $S.67\frac{1}{2}^{\circ}E.$, 97 lks. dist., marked T 19 S R 8 W S 20 B T.
 A cedar, 24 ins. diam., bears $S.85^{\circ}W.$, 61 lks. dist., marked T 19 S R 8 W S 19 B T.
 A cedar, 24 ins. dia., bears $N.66\frac{1}{4}^{\circ}W.$, 60 lks. dist., marked T 19 S R 8 W S 18 B T.