

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 8 W.

CHAINS	
28.25	Top of ridge, c N. & S., 250 ft. above last stream; descend along steep SW. slope.
39.72	Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, marked $\frac{1}{4}$ S on N. face; from which A cedar, 30 ins. dia., bears S.45°E., 25 lks. dist., marked $\frac{1}{4}$ S B T. A cedar, 12 ins. dia., bears N.45°W., 12 lks. dist., marked $\frac{1}{4}$ S B T.
41.70	Stream, 8 lks. wide, c S., 250 ft. below ridge; ascend along S. side of a little stream in very thick briars & brush.
51.25	Said stream, 2 lks. wide, c N.70°E.; ascend very steep.
62.55	Top of steep ascent; thence along steep S. slope, about 350 ft. above last stream.
79.44	Cor. to secs. 7, 8, 17 & 18.
	N.88°47'W., on random line, bet. secs. 7 & 18.
	Va.20°28'E. at 2 p.m.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
97.54	Intersect W. bdy. of Township at cor. to secs. 7 & 18; ran thence S.88°47'E., on true line, bet. secs. 7 & 18. Va.20°14'E. at 4 p.m. On high mountain; descend.
40.00	Into stream, 3 lks. wide, c E. from S.80°W., 900 ft. below cor.
43.50	Leave stream, c N.60°E.
44.75	Stream, 5 lks. wide, c SE. in slide.
46.00	Stream, 4 lks. wide, c S., coming over precipice; ascend.
52.50	Top of ascent, about 150 ft. up; thence along bench sloping S.
57.50	Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A fir, 14 ins. diam., bears N.41°W., 26 lks. dist., marked $\frac{1}{4}$ S B T.