

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

A fir, 10 ins. diam., bears S.49 $\frac{1}{2}$ °E., 20 lks. dist.,
marked $\frac{1}{4}$ S B T.

67.50 Descend on NE. slope.

78.75 Stream, 5 lks. wide, c SE., water of a pale milky color,
about 350 ft. down.

80.50 Stream, 2 lks. wide, c S.; ascend along S. slope.

97.54 The cor. to secs. 7, 8, 17 & 18.

Oct. 5th, '91.

N.5°W. bet. secs. 7 & 8.

Va.20°33'E. at 8 a.m.

Ascend.

9.00 Top of ridge, c N.80°E., 200 ft. above cor.; descend
very steep.21.00 Stream, 3 lks. wide, c N.70°E., 450 ft. below ridge;
ascend.

26.00 Top of spur, 100 ft. up, c E.; descend.

32.00 Fir, 24 ins. diam.

33.00 Stream, 5 lks. wide, c S.80°E., 200 ft. down; ascend.

40.00 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which
An alder, 12 ins. dia., bears S.48 $\frac{1}{2}$ °E., 50 lks.
dist., marked $\frac{1}{2}$ S B T.A fir, 20 ins. dia., bears N.66 $\frac{1}{2}$ °W., 42 lks. dist.,
marked $\frac{1}{4}$ S B T.

56.50 Descend.

61.50 Stream, 5 lks. wide, c E.; ascend very steep.

68.50 Top of ascent, 300 ft. up; thence on narrow bench
sloping E.

74.00 Into a stream, 3 lks. wide, c E., in a steep rocky trough.

80.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for
cor. to secs. 5, 6, 7 & 8, marked T 19 S S 5 on NE.,
R 8 W S 8 on SE., S 7 on SW., S 6 on NW. faces, with
5 notches on E. & S. edges; from which

An alder, 18 ins. diam., bears N.14°E., 24 lks.