

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

dist., marked T 19 S R 8 W S 5 B T.

A maple, 8 ins. dia., bears S.60°E., 38 lks. dist.,
marked T 19 S R 8 W S 8 B T.

An alder, 8 ins. dia., bears S.41°W., 43 lks. dist.,
marked T 19 S R 8 W S 7 B T.

A vine maple, 4 ins. dia., bears N.42°W., 50 lks.
dist., marked T 19 S R 8 W S 6 B T.

S.88°47'E., on random line, bet. secs. 5 & 8.

Va.20°31'E. at 10 a.m.

40.00 Set temp. 1/2 sec. cor.

79.20 Intersect N. & S. line, 30 lks. S. of cor. to secs. 4, 5,
8 & 9; thence run

N.89°W., on true line, bet. secs. 5 & 8.

Va.20°29'E. at 1 p.m.

Descend.

11.40 Stream, 3 lks. wide, c S., 250 ft. down; ascend very
steep.

18.50 Spur, c N.80°E.; continue to ascend steep.

31.50 Top of ridge, c S.20°E., 750 ft. up; descend steep.

40.00 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for
1/2 sec. cor., marked 1/4 S on N. face; from which

A fir, 14 ins. diam., bears S.21°E., 10 lks. dist.,
marked 1/4 S B T.

A fir, 12 ins. diam., bears N.32 1/2°W., 28 lks. dist.,
marked 1/2 S B T.

42.00 Bottom of hollow, c S., 300 ft. down; ascend steep.

47.25 Onto spur, c E., 200 ft. up; descend.

56.25 Stream, 4 lks. wide, c S., in a slide, 250 ft. down.

57.75 Stream, 2 lks. wide, c S.

59.00 Stream, 4 lks. wide, c S.20°E., in rock slide; ascend
steep.

68.25 Rock bluff, 30 ft. high; thence continue to ascend along
very steep S. slope.

79.20 The cor. to secs. 5, 6, 7 & 8, 700 ft. above stream.

Oct. 6th, '91.