

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 8 W.

CHAINS

- N.88°47'W., on a random line, bet. secs. 6 & 7.
- Va.20°33'E. at 7 a.m.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 96.75 Intersect Tp. line, 7 lks. N. of cor. to secs. 6 & 7;
thence run
S.88°50'E., on true line, bet. secs. 6 & 7.
- Va. at 11 a.m. 20°20'E.
- Descend gently through fine green timber.
- 7.75 Stream, 6 lks. wide, c N.20°W.; ascend gently.
- 20.90 Fir, 24 ins. diam.; continue to ascend gently through
thick elk brush & fine timber.
- 48.00 Top of ridge, c N. & S., 600 ft. above last stream, with
open grassy glades along top, known as Elk ridge; de-
scend gently among small timber and dense salal brush.
- 56.75 Set post, 4 ft. long, 3 ins. sq., 24 ins. in ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which
A fir, 20 ins. diam., brs. N.12°E., 25 lks. dist.,
marked $\frac{1}{4}$ S B T.
A fir, 10 ins. diam., bears S.29°W., 19 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 63.00 Stream, 4 lks. wide, c N.60°E., 400 ft. down; ascend
along N. slope, heavy timber.
- 78.75 Stream, 3 lks. wide, c N.70°W.; ascend very steep.
- 89.50 Top of high ridge, 400 ft. up, c N. & S., in dead brush,
broad top.
- 91.00 Descend very steep.
- 96.75 To cor. to secs. 5, 6, 7 & 8, 250 ft. down.

Oct. 7, '91.

Extracts from Subdivisions of T. 19 S., R. 7 W., W.M.
Survey by Charles M. Collier under Contract 580 dated
June 23rd, 1891.

West, on line bet. secs. 30 & 31.

* * * * *

- 52.20 Intersect East boundary of T. 19 S., R. 8 W., 5.00 chs.
South of $\frac{1}{4}$ sec. cor. on E. bdy. of Sec. 25.
- At said intersection, set post, 4 ft. long, 4 ins. sq.,