

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20 S., R. 6 W.

CHAINS

North between Secs. 19 & 24.

Va.19°30'E.

- 30.25 Canyon, bears S.70°W. -200
- 40.00 Post for 1/2 sec. corner; from which +200
  - A fir, 5 ins. diam., bears S.10°E., 11 lks. dist.
  - A fir, 18 ins. dia., bears N.5°W., 20 lks. dist.
- 79.50 Brook, 3 lks. wide, runs East. -200
- 80.00 Set post for corner to secs. 18, 19, 23 & 24; from which +50
  - A fir, 30 ins. dia., bears S.80°E., 24 lks. dist.
  - A fir, 48 ins. dia., bears N.5°W., 50 lks. dist.
  - A maple, 4 ins. dia., bears S.45°W., 40 lks. dist.
  - A maple, 3 ins. dia., bears N.18°E., 36 lks. dist.

North between secs. 13 & 18.

Va.19°35'E.

- 40.00 Set sandstone, 18x13x7 ins., for 1/2 sec. corner.
- 80.00 Set post for corner to secs. 7, 12, 13 & 18; from which
  - A fir, 9 ins. diam., bears S.46°E., 21 lks. dist.
  - A fir, 40 ins. dia., bears N.6°E., 11 lks. dist.
  - A fir, 9 ins. dia., bears N.85°W., 60 lks. dist.
  - A fir, 60 ins. dia., bears S.34°W., 105 lks. dist.

Extracts from field notes of South Bdy. of T. 19 S., R. 7 W. as surveyed by H. C. and Joseph Perkins under Contract 203 dated March 14th, 1874.

West along south boundary of Sec. 34.

\* \* \* \* \*

- 80.00 Set maple post for cor. to secs. 3, 4, 33 and 34; from which
  - A maple, 4 ins. dia., bears N.45°E., 18 lks. dist.
  - A dogwood, 5 ins. dia., bears S.25°E., 45 lks. dist.
  - A vine maple, 4 ins. dia., bears S.60°W., 50 lks. dist.
  - A maple, 8 ins. dia., bears N.30°W., 32 lks. dist.

April 30th, 1874.