

County Surveyor's Record, Douglas County, Oregon

Exteriors of T. 21 S., R. 7 W.
 Survey by L. H. Wheeler under Contract 467 dated April 7th, 1883.
 East Bdy.

CHAINS

I begin at the cor. to Town. 21 & 22 S., Rgs. 6 & 7 W.
 I found the post much decayed and one of the witness
 trees blown down. I reestablished the same by setting
 a post, 6 ins. dia., 4 ft. long, 24 ins. in ground,
 marked T 21 S S 31 on NE., R 6 W S 6 on SE., T 22 S S 1
 on SW., R 7 W S 36 on NW. face, with 6 notches on each
 edge; from which

Fir, 20 ins. dia., bears N.57°E., 56 lks. dist.,
 marked T 21 S R 6 W S 31 B T.

Cedar, 14 ins. dia., bears S.71°W., 10 lks. dist.,
 marked T 22 S R 7 W S 1 B T.

Fir, 40 ins. dia., bears S.23°E., 60 lks. dist.,
 marked T 22 S R 6 W S 6 B T.

Fir, 20 ins. dia., bears N.17°W., 80 lks. dist.,
 marked T 21 S R 7 W S 36 B T.

North between secs. 31 & 36.

V.20½°E.

Along West slope of mountain.

8.50 Cross branch, 4 lks. wide, course N.10°E.

16.00 Cross same branch, course NW.

22.50 Cross branch, 4 lks. wide, course West; along flat.

40.00 A hemlock, 8 ins. dia. for gr. sec. cor., marked ¼ S on
 West face; from which

A fir, 40 ins. dia., bears S.71°W., 54 lks. dist.,
 marked ¼ S B T.

A fir, 18 ins. dia., bears S.30°E., 5 lks. dist.,
 marked ½ S B T.

73.50 Cross stream, 36 lks. wide, course West; ascend.

80.00 Set post, 5 ins. dia., 4 ft. long, with marked stone, 12
 ins. in ground, for cor. to secs. 30, 31, 25 & 36,
 marked T 21 S S 30 on NE., R 6 W S 31 on SE., R 7 W S
 36 on SW., S 25 on NW. face, with one notch on S. and
 five on N. edge; from which

A fir, 20 ins. dia., bears S.10°W., 28 lks. dist.,
 marked T 21 S R 7 W S 36 B T.