

County Surveyor's Record, Douglas County, Oregon

East Bay. of T. 21 S., R. 7 W.

CHAINS

A fir, 20 ins. dia., bears N.64°E., 39 lks. dist.,
marked T 21 S R 6 W S 30 B T.

An alder, 8 ins. dia., bears N.68°W., 39 lks. dist.,
marked T 21 S R 7 W S 25 B T.

An alder, 6 ins. dia., bears S.30°E., 130 lks. dist.,
marked T 21 S R 6 W S 31 B T.

North between secs. 25 & 30.

V.20 $\frac{1}{2}$ °E.

Along ridge.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked $\frac{1}{2}$ S on West
face; from which

A burnt fir, 50 ins. dia., bears S.87°E., 77 lks.
dist., marked $\frac{1}{2}$ S B T.

A burnt fir, 24 ins. dia., bears N.87°W., 169 lks.
dist., marked $\frac{1}{2}$ S B T.

76.50 Cross branch, 2 lks. wide, course West.

80.00 Set post, 5 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for cor. secs. 24, 25, 19 & 30, marked
T 21 S S 19 on NE., R 6 W S 30 on SE., R 7 W S 25 on
SW., S 24 on NW. face, with two notches on the S. and
four on the N. edge; from which

A fir, 30 ins. dia., bears S.50°W., 43 lks. dist.,
marked T 21 S R 7 W S 25 B T.

A fir, 30 ins. dia., bears N.46°W., 94 lks. dist.,
marked T 21 S R 7 W S 24 B T.

A fir, 30 ins. dia., bears S.20°E., 15 lks. dist.,
marked T 21 S R 6 W S 30 B T.

An alder, 10 ins. dia., bears N.17°E., 25 lks. dist.,
marked T 21 S R 6 W S 19 B T.

North between secs. 24 & 19.

V.20 $\frac{1}{2}$ °E.

Along West slope.