

## County Surveyor's Record, Douglas County, Oregon

East Bay. of T. 21 S., R. 7 W.

CHAINS

- 63.50 Along creek, 10 lks. wide, flows N. from the SE.
- 80.00 A vine maple, 6 in. dia., for cor. to secs. 12, 13, 7 & 18, marked T 21 S S 7 on NE., R 6 W S 18 on SE., R 7 W S 13 on SW., S 12 on NW. face, with 4 notches on S. and 2 on N. edge; from which
- A fir, 20 ins. dia., bears N.20°W., 64 lks. dist., marked T 21 S R 7 W S 12 B T.
- A fir, 20 ins. dia., bears N.75°E., 70 lks. dist., marked T 21 S R 6 W S 7 B T.
- A fir, 24 ins. dia., bears S.53°E., 43 lks. dist., marked T 21 S R 6 W S 18 B T.
- A fir, 20 ins. dia., bears S.58°W., 44 lks. dist., marked T 21 S R 7 W S 13 B T.

---

North between secs. 7 & 12.

V.21°E.

Along creek, 10 lks. wide.

- 16.50 On East side of creek, course N.10°W.
- 32.50 Cross branch, 6 lks. wide, course West; ascend.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on W. face; from which
- A fir, 12 ins. dia., bears N.72°W., 30 lks. dist., marked  $\frac{1}{4}$  S B T.
- A fir, 48 ins. dia., bears N.28°E., 31 lks. dist., marked  $\frac{1}{4}$  S B T.
- 57.50 Cross spur; descend.
- 79.00 Cross gulch, course West; ascend.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 1, 12, 6 & 7, marked T 21 S S 6 on NE., R 6 W S 7 on SE., R 7 W S 12 on SW., S 1 on NW. face, with 5 notches on S. and 1 notch on N. edge; from which
- A fir, 20 in. dia., bears N.18°W., 25 lks. dist., marked T 21 S R 7 W S 1 B T.