

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 21 S., R. 7 W.

CHAINS

A fir, 20 ins. dia., bears N.72°E., 46 lks. dist.,
marked T 21 S R 6 W S 6 B T.

A fir, 20 ins. dia., bears S.43°E., 24 lks. dist.,
marked T 21 S R 6 W S 7 B T.

A maple, 6 ins. dia., bears S.79°W., 20 lks. dist.,
marked T 21 S R 7 W S 12 B T.

North between secs. 1 & 6.

V.20 $\frac{1}{2}$ °E.

Ascend mountain.

10.00 On top hill; thence along West slope.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked rock, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on West
face; from which

A fir, 24 in. dia., bears N.55°E., 47 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 24 in. dia., bears N.88°W., 41 lks. dist.,
marked $\frac{1}{4}$ S B T.

64.50 Cross stream, 30 lks. wide, course NW.

69.00 Cross same stream, course NE.

71.00 Cross same stream, course NW.

78.50 Cross trail, course N.5°W.

98.90 Intersect the south boundary of Township 20 S., Range 6
W., 20.30 chs. East of cor. to T. 20 S., Rs. 6 & 7 W.,
which cor. I found gone, but witness trees standing.
Re-established the same by setting post, 6 in. dia.,
4 ft. long, 24 ins. in ground, marked T 20 S S 31 on
NE., T 21 S R 7 W on S. face, R 7 W S 36 on NW. face;
from which old witness trees bear:

An alder, 20 ins. dia., bears N.45°W., 25 lks. dist.,
marked T 20 S R 7 W S 36 B T.

A vine maple, 7 in. dia., bears S.61°E., 40 lks.
dist., marked T 21 S R 6 W S 6 B T.

A vine maple, 8 in. dia., bears N.43°E., 4 lks.
dist., marked T 21 S R 6 W S 31 B T.