

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 21 S., R. 7 W.

CHAINS

Found no bearing tree to the SW.

At point of intersection I set triangular post, 6 ins. dia., 4 ft. long, 24 ins. in ground, for closing cor. to T. 21 S R 6 & 7 W., marked T 20 S R 6 W S 31 on N., R 6 W S 6 on SE., T 21 S S 1 on SW. face, with 6 notches on S., E. and W. edges; from which

A fir, 20 ins. dia., bears N.20°W., 19 lks. dist., marked T 20 S R 6 W S 31 B T.

A fir, 12 ins. dia., bears S.43°W., 14 lks. dist., marked T 21 S R 7 W S 1 B T.

A fir, 20 ins. dia., bears S.18°E., 45 lks. dist., marked T 21 S R 6 W S 6 B T.

North Bdy. of T. 21 S., R. 7 W.

Knowing, from the unusual length of this line, that it would be impracticable to run a random from the NW. cor. of this township, I run West on a true line.

June 9, 1883.

West, on a true line, on the North boundary of Sec. 1.

V.21°E.

Descend.

11.00	In bottom.
20.30	The cor. to T. 20 S., Rs. 6 & 7 W.
20.80	Cross Smiths River, course North, 40 lks. wide.
30.50	Cross branch, 4 lks. wide, course N.80°E., along S. slope.
40.00	Set post, 4 in. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
	A fir, 24 in. dia., bears N.28°E., 12 lks. dist., marked $\frac{1}{4}$ S B T.
	A fir, 24 ins. diam., bears S.32°W., 49 lks. dist., marked $\frac{1}{4}$ S B T.
60.50	Cross ridge, course SW. & NE.; thence along North slope.
80.00	Set post, 6 ins. dia., 4 ft. long, 24 ins. in ground,