

## County Surveyor's Record, Douglas County, Oregon

West. Bdy. of T. 21 S., R. 7 W.

CHAINS

marked T 22 S R 8 W S 1 B T.

Thence I run .

North between secs. 31 &amp; 36.

V.  $21\frac{1}{4}^{\circ}$  E.

Through timber.

- 8.00 A brook, 5 lks. wide, course S.  $10^{\circ}$  E.
- 10.30 Fir, 36 ins. dia.
- 40.00 Set post, 3 ins. dia., 4 ft. long, 24 ins. in ground, for  
qr. sec. cor., marked  $\frac{1}{4}$  S on W. face; from which  
A fir, 36 ins. dia., bears N.  $35^{\circ}$  W., 36 lks. dist.,  
marked  $\frac{1}{4}$  S B T.  
A fir, 24 ins. dia., bears N.  $80^{\circ}$  E., 27 lks. dist.,  
marked  $\frac{1}{4}$  S B T.
- 52.00 A ridge, course N.  $70^{\circ}$  W.
- 62.00 A canyon, course N.  $70^{\circ}$  W.
- 80.00 Set post, 4 ins. dia., 4 ft. long, 24 ins. in ground, for  
cor. to secs. 25, 30, 31 & 36, marked T 21 S S 30 on  
NE., R. 7 W S 31 on SE., R 8 W S 36 on SW., S 25 on NW.  
face, with 5 notches on N. and 1 on S. edge; from which  
A fir, 7 in. dia., bears N.  $77^{\circ}$  E., 17 lks. dist.,  
marked T 21 S R 7 W S 30 B T.  
A fir, 7 ins. dia., bears S.  $57^{\circ}$  E., 9 lks. dist.,  
marked T 21 S R 7 W S 31 B T.  
A fir, 4 ins. dia., bears S.  $13^{\circ}$  W., 200 lks. dist.,  
marked T 21 S R 8 W S 36 B T.  
A fir, 24 ins. dia., bears N.  $25^{\circ}$  W., 73 lks. dist.,  
marked T 21 S R 8 W S 25 B T.

North between secs. 25 &amp; 30.

V.  $21\frac{1}{2}^{\circ}$  E.

Through timber.

- 6.00 A brook, 3 lks. wide, course NW.
- 18.50 Cross ridge, course E. & W.
- 27.55 A brook, 10 lks. wide, course S.  $80^{\circ}$  W.
- 40.00 Set post, 4 ins. dia., 4 ft. long, 24 ins. in ground, for