

## County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 21 S., R. 7 W.

CHAINS

- qr. sec. cor., marked  $\frac{1}{4}$  S on W. face; from which  
 A laurel, 5 ins. dia., bears S.20°E., 13 lks. dist.,  
 marked  $\frac{1}{4}$  S B T.  
 A dogwood, 4 ins. dia., bears S.72°W., 118 lks. dist.,  
 marked  $\frac{1}{4}$  S B T.
- 70.00 A ridge, NW. & SE.
- 80.00 Set post, 4 ins. dia., 4 ft. long, 24 ins. in ground, for  
 cor. to secs. 19, 24, 25 & 30, marked T 21 S S 19 on  
 NE., R 7 W S 30 on SE., R 8 W S 25 on SW., S 24 on NW.  
 face, with 4 notches on the N. & 2 notches on S. edges;  
 from which  
 A fir, 6 ins. dia., bears N.38°E., 220 lks. dist.,  
 marked T 21 S R 7 W S 19 B T.  
 A fir, 24 ins. dia., bears S.52°E., 50 lks. dist.,  
 marked T 21 S R 7 W S 30 B T.  
 A fir, 30 ins. dia., bears S.25°W., 46 lks. dist.,  
 marked T 21 S R 8 W S 25 B T.  
 A fir, 30 ins. dia., bears N.42°W., 80 lks. dist.,  
 marked T 21 S R 8 W S 24 B T.
- 
- North bet. secs. 19 & 24.  
 V.21 $\frac{1}{2}$ °E.  
 Through timber.
- 13.00 A brook, 2 lks. wide, course SE.
- 37.00 A ridge, course N.10°E.
- 40.00 Set post, 4 ins. dia., 4 ft. long, 24 ins. in ground,  
 for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on W. face; from which  
 A fir, 18 ins. dia., bears N.21°E., 25 lks. dist.,  
 marked  $\frac{1}{4}$  S B T.  
 A fir, 12 ins. dia., bears S.50°., 7 lks. dist.,  
 marked  $\frac{1}{4}$  S B T.
- 80.00 Set post, 4 ins. dia., 4 ft. long, 24 ins. in ground,  
 for cor. to secs. 13, 18, 19 & 24, marked T 21 S S 18  
 on NE., R 7 W S 19 on SE., R 8 W S 24 on SW., S 13 on  
 NW. face, with 3 notches on N. and 3 on S. edge; from  
 which