

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 21 S., R. 7 W.

CHAINS

- 12.50 Smiths River, 150 lks. wide, course West.
- 40.00 Set post, 3 in. dia., 4 ft. long, 24 ins. in ground, for
gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which
A fir, 5 ins. dia., bears N.31°E., 5 lks. dist.,
marked $\frac{1}{4}$ S B T.
A fir, 10 ins. dia., bears S.55°W., 41 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 65.00 A brook, 10 lks. wide, flows S.20°W.
- 79.00 Same brook, flows S.20°E.
- 98.00 Intersect North boundary of township, 74.25 chs. west of
the cor. to secs. 5 & 6.
Set post, 6 ins. dia., 5 ft. long, 12 ins. in ground, with
marked stone, marked on the NE., T 20 S S 31; R 7 W S
6 on SE., T 21 S S 1 on SW., R 8 W S 36 on NW. face,
with 6 notches on each edge; raised mound of stone
alongside; pits impracticable.

June 14, 1883.

Exterior Lines of T. 20 S., R. 7 W. as surveyed
by Thos. E. Todd under Contract 574 dated May 19th, 1891.
North Bdy.

Survey commenced July 27, 1891, at the cor. to secs. 3,
4, 33 & 34, on the N. bdy. of T. 20 S., R. 7 W. I find
this cor., a post set firmly in the ground, marked T
19 S S 34 on NE., R. 7 W S 3 on SE., T 20 S S 4 on SW.,
S 33 on NW. faces, with 3 notches on E. & W. edges;
from which
A maple, 4 ins. dia., bears N.45°E., 18 lks. dist.,
marked T 19 S R 7 W S 34 B T.
A dogwood, 5 ins. diam., bears S.25°E., 45 lks. dist.,
marked T 20 S R 7 W S 3 B T.
A V. maple, 4 ins. dia., bears S.60°W., 50 lks. dist.,
marked T 20 S R 7 W S 4 B T.
A maple, 8 ins. dia., bears N.30°W., 32 lks. dist.,
marked T 19 S R 7 W S 33 B T.

I run West, on a true line, on S. bdy. of Sec. 33, T. 19