

North Bdy. of T. 20 S., R. 7 W.

CHAINS

7 W on N., S 32 on W., S 31 on E. faces, with 4 notches on E. & 2 notches on W. faces; from which

A fir, 40 ins. dia., bears N.12°E., 47 lks. dist., marked T 19 S R.7 W S 33 B T.

A fir, 36 ins. dia., bears N.26°W., 14 lks. dist., marked T 19 S R 7 W S 32 B T.

A fir, 48 ins. dia., bears S.12°W., 45 lks. dist., marked T 19 S R 7 W S 32 & 33 B T.

July 27, 1891.

Thence I run

W., on a true line, S. bdy. of Sec. 32.

Va. 21°10'E.

Continue along N. slope.

4.25	Canyon with a little water.	-100
10.00	Divide, c NE. & SW.	+150
15.00	Va. 21°15'E.	
18.00	Divide, c NW. & SE.	
22.00	Stream, 2 lks. wide, c N.10°W.	-75
23.50	Stream, 2 lks. wide, c N.20°E.	
28.00	Spur, c N. & S.	+75
32.40	Canyon, c N.70°W.	-250
40.00	A sandstone in place, showing face 16x12 ins., 10 ins. above ground, which I mark with cross (x) at exact corner point, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which	
	A fir, 7 ins. dia., bears N.30°W., 10 lks. dist., marked $\frac{1}{4}$ S B T.	
	A fir, 48 ins. dia., bears S.20°E., 35 lks. dist., marked $\frac{1}{4}$ S B T.	
40.75	Descend slope.	
43.30	Canyon, c N.	-180
47.75	A fir, 50 ins. dia., on line, which I marked with 2 notches on E. & W. sides.	
49.30	Top of spur, c N.30°E.	+325