

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 20 S., R. 7 W.

CHAINS

A cherry, 10 ins. dia., bears S.35°E., 29 lks. dist.,
marked T 20 S R 7 W S 6 B T.

A hemlock, 4 ins. dia., bears S.61°W., 28 lks. dist.,
marked C C T 19 & 20 S R 7 W B T.

July 29, 1891.

South Bdy.

I go to the SE. cor. of T. 20 S., R. 7 W., which is a
post, 4 ins. square, firmly set in the ground, marked
T 20 S S 31 on NE., R 6 W S 6 on SE., T 21 S S 1 on SW.,
R 7 W S 36 on NW. faces, with 6 notches on each edge;
from which

An alder, 16 ins. dia., bears N.45°W., 25 lks. dist.,
marked T 20 S R 7 W S 36 B T.

A V. maple, 6 ins. dia., bears S.6°E., 18 lks. dist.,
(not S.61°E., 40 lks. dist.) marked T 21 S R 6 W
S 6 B T.

An alder, 14 ins. dia., bears S.67°W., 29 lks. dist.,
(lying down) marked T 21 S R 7 W S 1 B T.

A V. maple, 7 ins. dia., bears N.43°E., 24 lks. dist.,
(not 34 lks.) marked T 20 S R 6 W S 31 B T.

I retrace the S. bdy. of Sec. 36 & find it crooked; I,
therefore, run a trial line the entire distance along
the south bdy. of the Tp., as follows:

I commence at the above described SE. cor. of T. 20 S.,
R. 7 W. & run
W. along N. bdy. of Sec. 1, T. 21 S., R. 7 W.

at 21 chs. I find $\frac{1}{4}$ sec. cor. to Sec. 1 bears S., 3 lks.
dist.; at 61.30 chs. the cor. to secs. 1 & 2 bears S.
3 lks. dist.

I here offset S. 10 lks. to cor. & run W. on N. bdy. of
Sec. 2.
at 40.40 chs. the $\frac{1}{4}$ sec. cor. to Sec. 2 bears S. 70 lks.
dist.

The true bearing of the S. bdy. of Sec. 36 is, therefore,
practically S.89°45'W. and the township on the south
having been surveyed, and this line closed upon, I
could not change its course nor alignment.

I continue W. on a true line on N. bdy. of Sec. 2; at
80.90 chs. find cor. to secs. 2 & 3 bears S., 140 lks.
dist. I here offset S. 140 lks. to cor. and run W.