

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 7 W.

CHAINS		
	for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A maple, 8 ins. dia., bears S.34°E., 26 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 28 ins. dia., bears N.12°W., 20 lks. dist., marked $\frac{1}{4}$ S B T.	
45.00	Top of spur, c NE.; descend.	+50
53.50	Canyon, c N.	-300
61.30	Cor. to secs. 1 & 2, which is a post, 6 ins. dia., firmly set in the ground, marked T 20 S R 7 W S 36 on N., R 7 W S 1 on SE., T 21 S S 2 on SW. faces, with 1 notch on E. & 5 notches on W. edges; from which A fir, 10 ins. dia., bears N.65°E., 26 lks. dist., marked T 20 S R 7 W S 36 B T. A fir, 16 ins. dia., bears S.63°W., 12 lks. dist., marked T 21 S R 7 W S 2 B T. A fir, 16 ins. dia., bears S.6°E., 42 lks. dist., marked T 21 S R 7 W S 1 B T.	
67.25	Canyon, c N.80°E.	-250
76.00	Top of divide, c N.10°E.	+400
80.00	Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 35 & 36, marked T 20 S R 7 W on N., S 36 on E., S 35 on W. faces, with 1 notch on E. and 5 notches on W. faces; from which A fir, 30 ins. dia., bears N.6°W., 45 lks. dist., marked T 20 S R 7 W S 35 B T. A fir, 9 ins. dia., bears N.75°E., 58 lks. dist., marked T 20 S R 7 W S 36 B T. A fir, 8 ins. dia., bears S.46°E., 38 lks. dist., marked T 20 S R 7 W S 35 & 36 B T.	
	Aug. 3, 1891.	
	S.89°W., on S. bdy. of Sec. 35. Va.21°15'E.	
15.00	Stream, 1 lk. wide, c N.80°W.	-40
21.50	Stream, 4 lks. wide, c N.	-20