

## County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 7 W.

CHAINS		
21.80	A V. maple, 5 ins. dia. for $\frac{1}{4}$ sec. cor. to sec. 2, marked $\frac{1}{4}$ S on N. face; from which A fir, 40 ins. dia., bears N., 8 lks. dist., marked $\frac{1}{4}$ S B.T. A fir, 48 ins. dia., bears S.45°E., 2 lks. dist., marked $\frac{1}{4}$ S B T.	
28.00	Spur, c N.25°E.	+125
33.00	Canyon, c N.45°E.	-30
40.00	Set post, 4 ft. long, 4 ins. square, 2 ft. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A fir, 20 ins. dia., bears N.33°E., 7 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 24 ins. dia., bears S.24°E., 10 lks. dist., marked $\frac{1}{4}$ S B T.	
	Situated at head of spur, c N.	+300
42.00	Top of ridge, c S.65°E.	
58.00	Top of ridge, c S.65°W.; descend.	-50
62.25	Cor. to secs. 2 & 3, T. 21 S., R. 7 W., which is a post, 6 ins. dia., firmly set, 2 ft. above ground, marked T 20 S R 7 W S 35 on N., R 7 W S 2 on SE., T 21 S S 3 on SW. faces, with 2 notches on E. & 4 notches on W. edges; from which A fir, 36 ins. dia., bears N.15°E., 31 lks. dist., marked T 20 S R 7 W S 35 B T. A fir, 30 ins. dia., bears S.81°E., 5 lks. dist., marked T 21 S R 7 W S 2 B T. A fir, 20 ins. dia., bears S.65°W., 37 lks. dist., marked T 21 S R 7 W S 3 B T.	
69.20	Small canyon, c SW.	
80.00	Set post, 4 ft. long, 4 ins. square, 24 ins. in ground, for cor. to secs. 34 & 35, marked T 20 S R 7 W on N. face, S 34 on W., S 35 on E. faces, with 2 notches on E. & 4 notches on W. faces; from which A maple, 12 ins. dia., bears N.62°E., 74 lks. dist., marked T 20 S R 7 W S 35 B T.	