

County Surveyor's Record, Douglas County, Oregon

South Bay. of T. 20 S., R. 7 W.

CHAINS

A chinquapin, 6 ins. dia., bears S.22°W., 49 lks. dist., marked T 20 S R 7 W S 34 & 35 B T.

A fir, 30 ins. dia., bears N.58°W., 72 lks. dist., marked T 20 S R 7 W S 34 B T.

Aug. 4, 1891.

S.89°W., on S. bdy. of Sec. 34.

Va.21°15'E.

- 6.00 Stream, 3 lks. wide, c S.35°E. -100
- 11.25 Stream, 4 lks. wide, c S.82°E.
- 22.75 A post marked $\frac{1}{4}$ S on N. face, for $\frac{1}{4}$ sec. cor. to Sec. 3, set firmly in the ground; from which
- A fir, 40 ins. dia., bears N.30°W., 23 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 36 ins. dia., bears S.51°E., 11 lks. dist., marked $\frac{1}{4}$ S B T.
- 30.75 Top of spur, c SE. +250
- 40.00 Marked sandstone in place, 24x24 ins. face in side of hill, for $\frac{1}{4}$ sec. cor., marked with cross (x) at exact corner point, $\frac{1}{4}$ on N. face; from which
- A fir, 30 ins. dia., bears N.65°E., 35 lks. dist., marked $\frac{1}{4}$ S B T.
- A maple, 6 ins. dia., bears S.75°W., 44 lks. dist., marked $\frac{1}{4}$ S B T.
- 40.30 Small canyon; ascend.
- 50.60 Spur, c S. +300
- 63.50 The cor. to secs. 3 & 4, which is a post, 5 ins. diam., firmly set 2 ft. above ground, marked T 20 S R 7 W S 34 on N., T 21 S S 4 on SW., R 7 W S 3 on SE. faces, with 3 notches on E. & W. edges; from which
- A maple, 14 ins. dia., bears S.14°E., 21 lks. dist., marked T 21 S R 7 W S 3 B T.
- A fir, 40 ins. dia., bears N.20°W., 72 lks. dist., marked T 20 S R 7 W S 34 B T.
- A fir, 36 ins. dia., bears S.45°W., 41 lks. dist.,