

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 7 W.

CHAINS

	ground, for cor. to secs. 4 & 5, marked T 20 S R 7 W S 33 on N., R 7 W S 4 on SE., T 21 S S 5 on SW. faces, with 2 notches on W. & 4 notches on E. edges; from which A maple, 24 ins. dia., bears N.27°E., 14 lks. dist., marked T 20 S R 7 W S 33 B T. A cedar, 30 ins. dia., bears S.34°E., 49 lks. dist., marked T 21 S R 7 W S 4 B T. A fir, 50 ins. dia., bears S.37°W., 20 lks. dist., marked T 21 S R 7 W S 5 B T.	
76.35	Top of spur, c N.; descend.	+150
80.00	Set cedar post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for cor. to secs. 32 & 33, marked T 20 S R 7 W on N., S 32 on W., S 33 on E. faces, with 2 notches on W. and 4 notches on E. faces; from which A cedar, 10 ins. dia., bears N.9°E., 25 lks. dist., marked T 20 S R 7 W S 33 B T. A fir, 12 ins. dia., bears S.27°W., 19 lks. dist., marked T 20 S R 7 W S 32 & 33 B T. A hemlock, 18 ins. dia., bears N.25°W., 45 lks. dist., marked T 20 S R 7 W S 32 B T. Aug. 5, 1891.	
	S.89°30'W., along S. bdy. S. 32. Va.21°15'E.	
	Ascend.	
5.25	Smith River, 80 lks. wide, c NE.	+150
6.50	Smith River; trail c along river.	
19.50	Top of spur, c S.	+150
25.30	A post, 4 ins. diam., set firmly in the ground, 2 ft. above ground, for $\frac{1}{4}$ sec. cor. to sec. 5, marked $\frac{1}{4}$ S on N. face; from which An alder, 20 ins. dia., bears N.12°E., 22 lks. dist., marked $\frac{1}{4}$ S B T. An alder, 20 ins. dia., bears S.5°W., 11 lks. dist., marked $\frac{1}{4}$ S B T.	
27.50	Smith River; trail c along river.	