

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 7 W.

CHAINS

16.50 Top of ridge, c S.80°W.; descend. +425

26.00 I here made diligent search for $\frac{1}{4}$ sec. cor. to sec. 6,
but was unable to find one.

39.00 Canyon, c N.25°E. -250

40.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground,
for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which
A fir, 70 ins. dia., bears N.30°E., 35 lks. dist.,
marked $\frac{1}{4}$ S B T.
A maple, 6 ins. dia., bears S.62°E., 88 lks. dist.,
marked $\frac{1}{4}$ S B T.

51.00 Stream, 2 lks. wide, c SW.

54.40 Closing cor. to Tps. 20 & 21 S., R. 7 W., which is de-
scribed as a post, 6 ins. dia., with mound of stone;
I find the post greatly decayed and the marks nearly
obliterated. I destroy all traces of old cor. and re-
establish it as follows:
Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground,
for closing cor. to Tps. 20 & 21 S., R. 7 W., marked
C C T 20 & 21 S R 7 W on E., T 21 S R 7 W S 6 on S., T
20 S R 7 W S 31 on N. face, with 6 notches on each face;
from which
A fir, 12 ins. dia., bears N.38°W., 50 lks. dist.,
marked C C T 20 & 21 S R 7 W B T.
A fir, 12 ins. dia., bears N.38°E., 55 lks. dist.,
marked T 20 S R 7 W S 31 B T.
A maple, 10 ins. dia., bears S.40°E., 40 lks. dist.,
marked T 21 S R 7 W S 6 B T.

Aug. 6, 1891.

West Bdy.

In attempting to close upon the W. bdy. of the township,
I reach it at 51.50 chs.; this being too short a dis-
tance, I went to the SW. cor. of the township and
starting from the corner I run
N., on a true line, along W. bdy. Sec. 31.