

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20 S., R. 7 W.

CHAINS

The true bearing of the E. bdy. of Sec. 13 is, therefore,
N.1°E.

I here offset E. 140 lks. to cor.

Sept. 15, 1891.

N. on E. bdy. of Sec. 12, T. 20 S., R. 8 W.

Va.20°55'E.

25.70	Top of ridge, c W.; descend.	+30
39.50	Stream, 2 lks. wide, c W.	-30
40.30	To a point 70 lks. West of a post, 4 ins. dia., firmly set in the ground, for $\frac{1}{2}$ sec. cor., marked $\frac{1}{2}$ S on W. face; from which <p style="margin-left: 40px;">A fir, 12 ins. dia., bears S.65°E., 13 lks. dist., marked $\frac{1}{2}$ S B T. A fir, 40 ins. dia., bears S.52°W., 7 lks. dist., marked $\frac{1}{2}$ S B T.</p>	+300
46.25	Stream, 4 lks. wide, c SW.	-300
80.25	To a point 140 lks. West of a post, 4 ins. dia., firmly set in the ground, for cor. to secs. 1 & 12, marked T 20 S R 7 W S 7 on E., T 20 S R 8 W S 12 C C on SW., S 1 C C on NW. faces, with 1 notch on N. & 5 notches on S. edges; from which <p style="margin-left: 40px;">A fir, 48 ins. dia., bears N.74°E., 38 lks. dist., marked T 20 S R 7 W S 7 B T. A cedar, 18 ins. dia., bears S.28°W., 42 lks. dist., marked T 20 S R 8 W S 12 B T. A cedar, 20 ins. dia., bears N.64°W., 16 lks. dist., marked T 20 S R 8 W S 1 B T.</p>	

Therefore the true bearing of the E. bdy. of Sec. 12 is
N.1°E.

I here offset 140 lks. E. to cor.

Sept. 16, 1891.

N. on E. bdy. Sec. 1, T. 20 S., R. 8 W.

Va.20°45'E.