

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20 S., R. 7 W.

CHAINS

- 3.15 Stream, 5 lks. wide, c W.
- 29.60 Spur, c W. +200
- 40.25 To a point 80 lks. West of a post, 4 ins. dia., firmly set in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- A fir, 8 ins. dia., bears S.68°E., 12 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 10 ins. dia., bears S.63°W., 12 lks. dist., marked $\frac{1}{4}$ S B T.
- 62.30 Stream, 4 lks. wide, c NW. -300
- 75.40 Stream, 10 lks. wide, c W.; ascend,
- 80.30 To a point 185 lks. West of the closing cor. to townships 19 & 20 S., R. 8 W., heretofore described.
- The true course of the E. bdy. of Sec. 1 is N.1°19'E.
- Sept. 16, 1891.

East Bdy.

I start at the SE. cor. of T. 20 S., R. 7 W. and run N. on a trial line and find the E. bdy. of Sec. 36 to be 83.12 chs. in length; I, therefore, start again at the same cor. and reestablish the said line, continuing North to-wit:

N. on true line, E. bdy. Sec. 36.

Va.21°15'E.

Along blazed line.

- 3.80 Smith River, 40 lks. wide, c N.10°E.
- 17.70 Smith River, 40 lks. wide, c N.80°W.
- 35.00 Smith River, 50 lks. wide, c N.30°E.
- 40.00 Set a post, 4 ft. long, 4 ins. square, 2 ft. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- A fir, 20 ins. dia., bears N.21°E., 17 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 20 ins. dia., bears N.48°W., 36 lks. dist., marked $\frac{1}{4}$ S B T.