

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 20 S., R. 7 W.

CHAINS

- 43.40 Old $\frac{1}{4}$ sec. cor. to Sec. 31, R. 6 W., which is a post, 3 ins. square, firmly set in the ground, marked $\frac{1}{4}$ S on W. face; from which
- A fir, 14 ins. dia., bears N.55°E., 20 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 12 ins. dia., bears N.61°W., 22 lks. dist., marked $\frac{1}{4}$ S B T.
- 48.30 Smith River, c S.80°W., 50 lks. wide.
- 66.75 Stream, 2 lks. wide, c SW.
- 70.65 Top of ridge, c SW.
- 80.00 Set sandstone, 30x16x8 ins., 22 ins. in the ground, for cor. to secs. 25 & 36, marked with 1 notch on S. and 5 notches on N. faces; from which
- A fir, 24 ins. dia., bears S.12°E., 17 lks. dist., marked T 20 S R 7 W S 25 & 36 B T.
- A maple, 12 ins. dia., bears S.54°W., 55 lks. dist., marked T 20 S R 7 W S 36 B T.
- A fir, 14 ins. dia., bears N.9°W., 27 lks. dist., marked T 20 S R 7 W S 25 B T.

+50

Aug. 3, 1891.

Thence N., on a true line, bet. secs. 25 & 30.

Va.20°45'E.

Along blazed line.

- 3.12 The old cor. to secs. 30 & 31, R. 6 W., where I find the post decayed. Set a sandstone, 24x16x8 ins., 18 ins. in the ground, marked with 1 notch on S. and 5 notches on N. faces; from which
- A fir, 24 ins. dia., bears N.37 $\frac{1}{2}$ °E., 19 lks. dist., marked T 20 S R 6 W S 30 B T.
- A fir, 24 ins. dia., bears S.56°E., 22 lks. dist., marked T 20 S R 6 W S 31 B T.
- A fir, 24 ins. dia., bears S.34°W., 75 lks. dist., marked T 20 S R 7 W S 36 B T.
- A maple, 10 ins. dia., bears N.14°W., 24 lks. dist.,