

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 7 W.

CHAINS		
		Va. 21°15'E.
	Ascend.	
.50	Top of ridge, c N.65°E.	+10
18.00	Ravine, c N.32°W.; ascend.	-200
33.50	Top of spur, c N.31°W.; descend.	+75
40.00	Set sandstone, 30x20x10 ins., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which A fir, 54 ins. dia., bears S.5°E., 10 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 48 ins. dia., bears N.8°W., 120 lks. dist., marked $\frac{1}{4}$ S B T.	
40.50	Canyon, c W.; ascend.	-175
49.80	Pin, 60 ins. dia., on line with 2 notches on N. & S. sides.	
70.50	Top of ridge, c S.15°E.; along S. slope.	+150
78.00	Top of same ridge, c S.15°W.	
80.00	Set sandstone, 24x10x10 ins., 18 ins. in the ground, for cor. to secs. 25, 26, 35 & 36, marked with 1 notch on S. & E. edges; from which A fir, 12 ins. dia., bears N.54°E., 6 lks. dist., marked T 20 S R 7 W S 25 B T. A fir, 8 ins. dia., bears S.39°E., 7 lks. dist., marked T 20 S R 7 W S 36 B T. A fir, 14 ins. dia., bears S.61°W., 9 lks. dist., marked T 20 S R 7 W S 35 B T. A fir, 20 ins. dia., bears N.40°W., 19 lks. dist., marked T 20 S R 7 W S 26 B T.	

Sept. 4, 1891.

N.89°45'E., on random line, bet. secs. 25 &amp; 36.

Va. 21°15'E.

40.00	Set temporary $\frac{1}{4}$ sec. cor.	
79.90	Intersect E. bdy. of the Township, 12 lks. S. of cor. to secs. 25 & 36.	

Thence I run

S.89°40'W., on true line, bet. secs. 25 &amp; 36.