

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 7 W.

CHAINS

Va. 20°45'E.

- 6.00 Enter J. W. Newman's enclosure, containing meadow and garden.
- 38.40 Leave enclosure; cross Smith River, 60 lks. wide, c N.
- 39.95 In Smith River, 70 lks. wide, c N., an impracticable place to set corner.
- 40.40 Set a sandstone, 30x14x10 ins., 22 ins. in the ground, for witness cor. to  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S W C on N. face. The  $\frac{1}{4}$  sec. cor. is situated in Smith River, 45 lks. E. of the witness cor., from which witness corner  
 A fir, 24 ins. diam., bears N.89°W., 52 lks. dist., marked  $\frac{1}{4}$  S W C B T.  
 A fir, 24 ins. diam., bears S.26°E., 50 lks. dist., marked  $\frac{1}{4}$  S W C B T.
- Ascend.
- 49.00 Top of ridge, c N. +75
- Va. 21°15'E.
- 56.00 Stream, 4 lks. wide, c N.; ascend. -75
- 79.00 Top of ridge, c N.20°E. +300
- 79.90 The cor. to secs. 25, 26, 35 & 36.
- Sept. 4, 1891.

N.0°1'W., bet. secs. 25 &amp; 26.

Va. 21°15'E.

- 4.00 Descend.
- 13.60 Smith River, 60 lks. wide, c S.65°W.; ascend.
- 17.00 Stream, 3 lks. wide, c S.15°E.; at crossing of Smith River, trail at a small log ridge on W. edge of a small slashing in which a board cabin stands.
- 40.00 Set post, 4 ft. long, 4 ins. square, 2 ft. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on W. face; from which  
 A fir, 4 ins. diam., bears N.13°W., 23 lks. dist., marked  $\frac{1}{4}$  S B T.  
 A fir, 7 ins. dia., bears N.26 $\frac{1}{2}$ °E., 37 lks. dist., marked  $\frac{1}{4}$  S. B T.