

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS		
	A dogwood, 4 ins. dia., bears S.57°E., 44 lks. dist., marked $\frac{1}{4}$ S B T.	
41.50	Top of spur, c N.6°W.; descend.	+175
59.50	Panther Creek bottom.	-250
63.40	Panther Creek, 15 lks. wide, c SW.; ascend.	
76.00	Top of ridge, c SW.	+50
80.34	The cor. to secs. 23, 24, 25 & 26.	
	Sept. 17, 1891.	
	N.0°1'W., bet. secs. 23 & 24.	
	Va.20°10'E.	
	Ascend along W. slope of ridge.	
40.00	Set a sandstone, in place, 40x30x4 ins. above ground, which I mark with a cross (x) at exact corner point for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which A fir, 28 ins. dia., bears N.86°E., 30 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 18 ins. dia., bears S.40°W., 21 lks. dist., marked $\frac{1}{4}$ S B T.	
	Va.20°E.	
42.00	Top of ridge, c S.36°E.	+400
45.00	Descend.	
48.00	Canyon, c N.35°E.	-300
63.40	Canyon, c S.87°E.	
71.25	Ridge, c E.; descend.	+150
76.50	Stream, 2 lks. wide, c E.	-175
80.00	Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 13, 14, 23 & 24, marked T 20 S S 13 on NE., R 7 W S 24 on SE., S 23 on SW., S 14 on NW. faces, with 3 notches on S. & 1 notch on E. edges; from which A hemlock, 10 ins. dia., bears N.47°E., 10 lks. dist., marked T 20 S R 7 W S 13 B T. A yew, 6 ins. dia., bears S.84°E., 17 lks. dist., marked T 20 S R 7 W S 24 B T.	