

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS

A fir, 60 ins. dia., bears S.40°W., 35 lks. dist.,  
marked T 20 S R 7 W S 23 B T.

A cedar, 14 ins. dia., bears N.22°W., 35 lks. dist.,  
marked T 20 S R 7 W S 14 B T.

Sept. 18, 1891.

N.89°40'E., on random line, bet. secs. 13 & 24.

Va.20°45'E.

40.00 Set temporary 1/4 sec. cor.

80.40 Intersect E. bdy. of Township, 35 lks. N. of cor. to secs.  
13 & 24.

Thence I run

S.89°55'W., on true line, bet. secs. 13 & 24.

Va.20°45'E.

12.50 Enter Panther Creek bottom.

-75

27.00 Panther Creek, 15 lks. wide, c S.10°W.

40.20 Set sandstone, 20x14x6 ins., 16 ins. in the ground, for  
1/4 sec. cor., marked 1/4 on N. face; from which

A fir, 48 ins. dia., bears N.26°E., 83 lks. dist.,  
marked 1/4 S B T.

A maple, 4 ins. dia., bears S.45°E., 4 lks. dist.,  
marked 1/4 S B T.

A small ledge of sandstone, 6 lks. S., which I mark cross  
(x) W. C.

42.50 Top of ridge, c S.70°E.

+300

62.25 Stream, 3 lks. wide, c S.25°E.; ascend.

-300

80.40 The cor. to secs. 13, 14, 23 & 24.

Sept. 18, 1891.

N.0°01'W., bet. secs. 13 & 14.

Va.20°45'E.

10.00 Top of spur, c E.

+100

17.00 Canyon with a little water, c N.85°E.

-250

27.50 Canyon, c S.15°E.

+25

36.00 Top of divide bet. Smith & Siuslaw waters, c N.56°E.,

general c E. & W.

+250