

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 7 W.

CHAINS

S S 26 on NE., R 7 W S 35 on SE., S 34 on SW., S 27 on NW. faces, with 2 notches on E. and 1 notch on S. edges; from which

A dogwood, 4 ins. diam., bears N.32°E., 39 lks. dist., marked T 20 S R 7 W S 26 B T.

A fir, 3 ins. dia., bears S.45°E., 60 lks. dist., marked T 20 S R 7 W S 35 B T.

A fir, 48 ins. dia., bears S.32°W., 40 lks. dist., marked T 20 S R 7 W S 34 B T.

A fir, 60 ins. dia., bears N.40°W., 80 lks. dist., marked T 20 S R 7 W S 27 B T.

Sept. 5, 1891.

N.89°E., on a random line, bet. secs. 26 & 35.

Va.20°45'E.

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

80.40 Intersect N. & S. line, 23 lks. S. of the cor. to secs. 25, 26, 35 & 36.

I run S.88°50'W., on a true line, bet. secs. 26 & 35.

Va.21°10'E.

9.00 Top of spur, c N.43°W.; descend.

-30

Va.20°55'E.

30.00 Smith River bottom.

-200

40.20 Set post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on N. face; from which

A cedar, 24 ins. diam., bears S.30°W., 15 lks. dist., marked  $\frac{1}{4}$  S B T.

An ash, 20 ins. diam., bears N.52°E., 54 lks. dist., marked  $\frac{1}{4}$  S B T.

44.00 Smith River, 50 lks. wide, c SW.

45.00 Smith River trail c along river.

45.25 Ascend.

76.00 Top of ridge, c SW.

+90

80.40 The cor. to secs. 26, 27, 34 & 35.

Sept. 5, 1891.