

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 7 W.

CHAINS	S.89°W., on a true line, bet. secs. 23 & 26. Va.20°10'E.	
.70	Stream, 2 lks. wide, c S.10°W.	
10.00	Cross spur & descend.	+175
22.75	Stream, 4 lks. wide, c SE.	-75
40.05	A sandstone in place, 6x4x1.ft. above ground, marked with cross (x) at exact point for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; from which A fir, 14 ins. diam., bears S.88°E., 69 lks. dist., marked $\frac{1}{4}$ S B T. A maple, 4 ins. diam., bears N.1°E., 52 lks. dist., marked $\frac{1}{4}$ S B T.	+325
42.00	Top of divide, c N. & S.	+25
73.00	Haney Creek, 15 lks. wide, c S.	-400
80.10	The cor. to secs. 22, 23, 26 & 27. Sept. 22, 1891.	
<hr/>		
	N.0°2'W., on true line, bet. secs. 22 & 23. Va.20°10'E.	
	Descend.	
2.00	Small canyon, c NE.	-75
12.00	Pearl Creek, 8 lks. wide, c E. Thence along bed of Haney Creek, through swamps and beaver dams.	-50
40.00	This point being in the bed of Haney Creek, an impracticable place to set a cor., I mark an alder, 8 ins. dia. bears W., 27 lks. dist., marked $\frac{1}{4}$ S W C on E. side, for witness cor. to $\frac{1}{4}$ sec. cor.; from which (witness cor.) An alder, 10 ins. diam., bears S.80°E., 44 lks. dist., marked $\frac{1}{4}$ S B T W C. An alder, 14 ins. diam., bears N.70°W., 8 lks. dist., marked $\frac{1}{4}$ S B T W C.	
75.00	Haney Creek, c S.15°E.	
80.00	Set sandstone, 16x8x4 ins., 12 ins. in ground, for cor.	