

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS

A fir, 40 ins. dia., bears N.69°E., 71 lks. dist.,
marked T 20 S R 7 W S 22 B T.

A fir, 48 ins. dia., bears S.3°E., 84 lks. dist.,
marked T 20 S R 7 W S 27 B T.

A fir, 48 ins. dia., bears S.36°W., 19 lks. dist.,
marked T 20 S R 7 W S 28 B T.

A fir, 36 ins. dia., bears N.13°W., 27 lks. dist.,
marked T 20 S R 7 W S 21 B T.

Sept. 25, 1891.

N.89°E., on random line, bet. secs. 22 & 27.

Va.20°30'E.

40.00 Set temporary $\frac{1}{4}$ sec. cor.

80.10 Intersect N. & S. line, 35 lks. N. of cor. to secs. 22,
23, 26 & 27.

Thence I run

S.89°15'W., on true line, bet. secs. 22 & 27.

Va.20°10'E.

10.80 Spur, c N. +250

16.00 Canyon, c N. -150

21.50 Spur, c N. -150

26.50 Canyon, c N.20°E. -150

32.25 Spur, c N.20°E. -150

38.50 Canyon, c N.20°E. -150

40.05 Set sandstone, 24x16x10 ins., 18 ins. in the ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; from which

A fir, 10 ins. dia., bears N.35°E., 6 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 14 ins. dia., bears S.14°E., 14 lks. dist.,
marked $\frac{1}{4}$ S B T.

49.50 Top of divide, c S.55°E. +150

70.93 Stream, 2 lks. wide, c SE. -200

Va.20°30'E.

80.10 The cor. to secs. 21, 22, 27 & 28.

Sept. 25, 1891.