

Subdivisions of T. 20 S., R. 7 W.

CHAINS	dist., marked $\frac{1}{4}$ S B T. An ash, 20 ins. dia., bears N.12°W., 25 lks. dist., marked $\frac{1}{4}$ S B T.	
46.00	Smith River, 90 lks. wide, c NW. At top of an impassable bluff, 75 ft. high, along river bank; therefore, \perp offset N. 8 chs.	
52.50	S. 8 chs. to line. The general course of the river here is nearly due North for half a mile, making a large bend & coming back to line at 61.50 chs.	
56.00	Enter river bottom.	
61.50	Smith River, c S., 90 lks. wide.	-75
65.00	Smith River trail, c S.; ascend.	
79.70	The cor. to secs. 28, 29, 32 & 33. Sept. 9, 1891.	+75
<hr/>		
	N.0°3'W., bet. secs. 28 & 29. Va.21°15'E.	
20.00	Va. 20°45'E. Ascend SE. slope.	
40.00	Set a sandstone, 16x16x8 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which A fir, 24 ins. dia., bears N.56°W., 12 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 24 in. dia., bears S.31°E., 18 lks. dist., marked $\frac{1}{4}$ S B T.	+300
45.50	Top of divide bet. Yellow Creek & Smith River, c S.20°W. Descend W. slope.	+50
57.75	Canyon, c N.55°W.	-125
58.50	Enter green timber.	+75
60.75	Top of spur, c N.50°W.	+50
68.00	Canyon, c N.68°W.	-150
72.65	Top of spur, c W.	+100
74.40	A fir, 70 in. dia., on line, with 2 notches on N. & S. sides.	
79.00	Canyon, c W.	-200