

Subdivisions of T. 20 S., R. 7 W.

CHAINS		
59.00	Still descend less steeply.	
80.30	The cor. to secs. 20, 21, 28 & 29.	
	Oct. 12, 1891.	
<hr/>		
	N.0°3'W., bet. secs. 20 & 21.	
	Va.21°10'E.	
	Ascend gradually along W. slope.	
11.50	Highest point & descend.	+75
	Va.20°45'E.	
14.50	Canyon, c W.; ascend.	-75
20.00	Along W. slope ascending.	
28.75	Descend.	+300
38.00	Stream, 2 lks. wide, c S.60°W.	-300
40.00	Set sandstone, 24x12x10 ins., 18 ins. in the ground, for ¼ sec. cor., marked ¼ on W. face; from which A maple, 12 ins. dia., bears S.70°E., 24 lks. dist., marked ¼ S B T. A fir, 36 ins. dia., bears W., 58 lks. dist., marked ¼ S B T.	
48.75	A fir, 48 ins. dia., on line, with 2 notches on N. & S. sides. Continue to ascend.	
60.00	Top of ridge, c N. & S.; along top.	+600
74.50	Descend NW. slope.	
80.00	Set a sandstone, 24x16x7 ins., 18 ins. in the ground, for cor. to secs. 16, 17, 20 & 21, marked with 3 notches on S. & 4 notches on E. edges; from which A fir, 24 ins. dia., bears N.8°E., 40 lks. dist., marked T 20 S R 7 W S 16 B T. A fir, 24 ins. dia., bears S.9°E., 75 lks. dist., marked T 20 S R 7 W S 21 B T. A fir, 12 ins. dia., bears S.15°W., 88 lks. dist., marked T 20 S R 7 W S 20 B T. A maple, 4 ins. dia., bears N.12°W., 18 lks. dist., marked T 20 S R 7 W S 17 B T.	
	Oct. 13, 1891.	